

1M Pseudo Static RAM (131072x8) 32PIN 658128

型名	社名	温度範囲 (°C)	スイッチング特性										電源		入力 [*typ]			出力 [*typ]			備考
			TAAC max (ns)	TCAC max (ns)	T <sub>OE</sub> max (ns)	T <sub>OH</sub> min (ns)	T <sub>OD</sub> max (ns)	T <sub>WP</sub> min (ns)	T <sub>DS</sub> min (ns)	T <sub>DH</sub> min (ns)	T <sub>WD</sub> min (ns)	T <sub>WR</sub> max (ns)	VDD or VCC (V)	I <sub>DD</sub> max (mA)	I <sub>DD</sub> STANDBY (I <sub>SB</sub> /I <sub>SB2</sub> ) (mA)	V <sub>IL</sub> max (V)	V <sub>IH</sub> min (V)	C <sub>i</sub> max (pF)	V <sub>OL</sub> /I <sub>VOL</sub> max (V/mA)	V <sub>OH</sub> /I <sub>VOH</sub> min (V/mA)	
HM658128ADFP-10	HITACHI	0~70	100	30	0	30	30	25	0	0	4.5~5.5	85	2/0.2	0.8	2.2	8	0.4/2.1	2.4/1	10		
HM658128ADFP-12	HITACHI	0~70	120	40	0	35	35	30	0	0	4.5~5.5	85	2/0.2	0.8	2.2	8	0.4/2.1	2.4/1	10		
HM658128ADFP-8	HITACHI	0~70	80	30	0	30	30	25	0	0	4.5~5.5	85	2/0.2	0.8	2.2	8	0.4/2.1	2.4/1	10		
HM658128ADP-10	HITACHI	0~70	100	30	0	30	30	25	0	0	4.5~5.5	85	2/0.2	0.8	2.2	8	0.4/2.1	2.4/1	10		
HM658128ADP-12	HITACHI	0~70	120	40	0	35	35	30	0	0	4.5~5.5	85	2/0.2	0.8	2.2	8	0.4/2.1	2.4/1	10		
HM658128ADP-8	HITACHI	0~70	80	30	0	30	30	25	0	0	4.5~5.5	85	2/0.2	0.8	2.2	8	0.4/2.1	2.4/1	10		
HM658128ALFP-10	HITACHI	0~70	100	30	0	30	30	25	0	0	4.5~5.5	85	2/0.2	0.8	2.2	8	0.4/2.1	2.4/1	10		
HM658128ALFP-12	HITACHI	0~70	120	40	0	35	35	30	0	0	4.5~5.5	85	2/0.2	0.8	2.2	8	0.4/2.1	2.4/1	10		
HM658128ALFP-8	HITACHI	0~70	80	30	0	30	30	25	0	0	4.5~5.5	85	2/0.2	0.8	2.2	8	0.4/2.1	2.4/1	10		
HM658128ALP-10	HITACHI	0~70	100	30	0	30	30	25	0	0	4.5~5.5	85	2/0.2	0.8	2.2	8	0.4/2.1	2.4/1	10		
HM658128ALP-12	HITACHI	0~70	120	40	0	35	35	30	0	0	4.5~5.5	85	2/0.2	0.8	2.2	8	0.4/2.1	2.4/1	10		
HM658128ALP-8	HITACHI	0~70	80	30	0	30	30	25	0	0	4.5~5.5	85	2/0.2	0.8	2.2	8	0.4/2.1	2.4/1	10		
HM658128P-10	HITACHI	0~70			25			15		0	4.5~5.5	7.5	2/-	0.8	2.2	8	0.4/1	2.4/2.1	10	Refresh:512/8	
HM658128P-12	HITACHI	0~70			30			20		0	4.5~5.5	7.5	2/-	0.8	2.2	8	0.4/1	2.4/2.1	10		
HM658128P-15	HITACHI	0~70			35			25		0	4.5~5.5	7.5	2/-	0.8	2.2	8	0.4/1	2.4/2.1	10		
KM658128-8	SAM	0~70	80	30	25			50	25	0	4.5~5.5	70	2/1	0.8	2.4	8	0.4/2.1	2.4/1	10		
KM658128-10	SAM	0~70	100	30	25			60	30	0	4.5~5.5	60	2/1	0.8	2.4	8	0.4/2.1	2.4/1	10		
KM658128-12	SAM	0~70	120	40	30			65	30	0	4.5~5.5	50	2/1	0.8	2.4	8	0.4/2.1	2.4/1	10		
KM658128-8L	SAM	0~70	80	30	25			50	25	0	4.5~5.5	70	2/0.2	0.8	2.4	8	0.4/2.1	2.4/1	10		
KM658128-10L	SAM	0~70	100	30	25			60	30	0	4.5~5.5	60	2/0.2	0.8	2.4	8	0.4/2.1	2.4/1	10		
KM658128-12L	SAM	0~70	120	40	30			65	30	0	4.5~5.5	50	2/0.2	0.8	2.4	8	0.4/2.1	2.4/1	10		
LH5P8128-60	SHARP	0~70	60		25			30		0	4.5~5.5	104	0.2/-	0.8	2.4	5	0.4/4	2.4/1	10		
LH5P8128-80	SHARP	0~70	80		30			30		0	4.5~5.5	70	0.2/-	0.8	2.4	5	0.4/4	2.4/1	10		
LH5P8128-10	SHARP	0~70	100		35			30		0	4.5~5.5	60	0.2/-	0.8	2.4	5	0.4/4	2.4/1	10		
LH5P8128-60L	SHARP	0~70	60		25			30		0	4.5~5.5	104	0.1/-	0.8	2.4	5	0.4/4	2.4/1	10		
LH5P8128-80L	SHARP	0~70	80		30			30		0	4.5~5.5	70	0.1/-	0.8	2.4	5	0.4/4	2.4/1	10		
LH5P8128-10L	SHARP	0~70	100		35			30		0	4.5~5.5	60	0.1/-	0.8	2.4	5	0.4/4	2.4/1	10		
LH5P8129-60	SHARP	0~70	60		25			30		0	4.5~5.5	104	0.2/-	0.8	2.4	5	0.4/4	2.4/1	10		
LH5P8129-80	SHARP	0~70	80		30			30		0	4.5~5.5	70	0.2/-	0.8	2.4	5	0.4/4	2.4/1	10		
LH5P8129-10	SHARP	0~70	100		35			30		0	4.5~5.5	60	0.2/-	0.8	2.4	5	0.4/4	2.4/1	10		
LH5P8129-60L	SHARP	0~70	60		25			30		0	4.5~5.5	104	0.1/-	0.8	2.4	5	0.4/4	2.4/1	10		
LH5P8129-80L	SHARP	0~70	80		30			30		0	4.5~5.5	70	0.1/-	0.8	2.4	5	0.4/4	2.4/1	10		
LH5P8128-10L	SHARP	0~70	100		35	10		30		0	4.5~5.5	60	0.1/-	0.8	2.4	5	0.4/4	2.4/1	10		
TC518128AP/ASP/AF/AFW-10	TOSHIBA	0~70	100	100	40	30	30	70	35	0	4.5~5.5	40	2/1	0.8	2.4	7	0.4/4.2	2.4/5	7		
TC518128AP/ASP/AF/AFW-12	TOSHIBA	0~70	120	120	50	35	35	85	45	0	4.5~5.5	35	2/1	0.8	2.4	7	0.4/4.2	2.4/5	7		
TC518128AP/ASP/AF/AFW-80	TOSHIBA	0~70	80	80	35	25	25	60	30	0	4.5~5.5	50	2/1	0.8	2.4	7	0.4/4.2	2.4/5	7		
TC518128APL/AF/AFWL-10LV	TOSHIBA	0~70	50	50	40	30	30	70	35	0	4.5~5.5	60	1/0.2	0.8	2.4	7	0.4/4.2	2.4/5	7		
TC518128APL/AF/AFWL-12LV	TOSHIBA	0~70	60	60	50	35	35	85	45	0	4.5~5.5	50	1/2	0.8	2.4	7	0.4/4.2	2.4/5	7		
TC518128APL/AF/AFWL-80LV	TOSHIBA	0~70	40	40	35	25	25	60	30	0	4.5~5.5	70	1/0.2	0.8	2.4	7	0.4/4.2	2.4/5	7		
TC518128APL/ASPL/AF/AFWL-10	TOSHIBA	0~70	100	100	40	30	30	70	35	0	4.5~5.5	40	1/0.2	0.8	2.4	7	0.4/4.2	2.4/5	7		
TC518128APL/ASPL/AF/AFWL-12	TOSHIBA	0~70	120	120	50	35	35	85	45	0	4.5~5.5	35	1/0.2	0.8	2.4	7	0.4/4.2	2.4/5	7		
TC518128APL/ASPL/AF/AFWL-80	TOSHIBA	0~70	80	80	35	25	25	60	30	0	4.5~5.5	50	1/0.2	0.8	2.4	7	0.4/4.2	2.4/5	7		